

Rotec Blindflansche (Epoxid-Huntsman-Harz)

Drilling Standard: ANSI B16.47 Class 150



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
1	700	3	950	864	28	35	48	BFE-700-03/150
2	700	6	950	864	28	35	60	BFE-700-06/150
3	700	10	950	864	28	35	74	BFE-700-10/150
4	700	16	950	864	28	35	92	BFE-700-16/150
5	800	3	1085	978	28	41	60	BFE-800-03/150
6	800	6	1085	978	28	41	68	BFE-800-06/150
7	800	10	1085	978	28	41	85	BFE-800-10/150
8	800	16	1085	978	28	41	105	BFE-800-16/150
9	900	3	1190	1086	32	41	60	BFE-900-03/150
10	900	6	1190	1086	32	41	78	BFE-900-06/150
11	900	10	1190	1086	32	41	95	BFE-900-10/150
12	900	16	1190	1086	32	41	115	BFE-900-16/150
13	1000	3	1320	1200	36	41	68	BFE-1000-03/150
14	1000	6	1320	1200	36	41	85	BFE-1000-06/150
15	1000	10	1320	1200	36	41	105	BFE-1000-10/150
16	1000	16	1320	1200	36	41	130	BFE-1000-16/150

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

09-02-2024

Rotec Blindflansche (Epoxid-Huntsman-Harz)

Drilling Standard: ANSI B16.47 Class 150



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
17	1100	3	1430	1314	40	41	74	BFE-1100-03/150
18	1100	6	1430	1314	40	41	95	BFE-1100-06/150
19	1100	10	1430	1314	40	41	110	BFE-1100-10/150
20	1100	16	1430	1314	40	41	140	BFE-1100-16/150
21	1200	3	1540	1422	44	41	80	BFE-1200-03/150
22	1200	6	1540	1422	44	41	105	BFE-1200-06/150
23	1200	10	1540	1422	44	41	120	BFE-1200-10/150
24	1200	16	1540	1422	44	41	155	BFE-1200-16/150
25	1300	3	1660	1537	44	48	85	BFE-1300-03/150
26	1300	6	1660	1537	44	48	110	BFE-1300-06/150
27	1300	10	1660	1537	44	48	130	BFE-1300-10/150
28	1300	16	1660	1537	44	48	165	BFE-1300-16/150
29	1400	3	1780	1651	48	48	95	BFE-1400-03/150
30	1400	6	1780	1651	48	48	120	BFE-1400-06/150
31	1400	10	1780	1651	48	48	140	BFE-1400-10/150
32	1400	16	1780	1651	48	48	175	BFE-1400-16/150
33	1500	3	1890	1759	52	48	100	BFE-1500-03/150

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

Rotec Blindflansche (Epoxid-Huntsman-Harz)

Drilling Standard: ANSI B16.47 Class 150



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
34	1500	6	1890	1759	52	48	125	BFE-1500-06/150
35	1500	10	1890	1759	52	48	150	BFE-1500-10/150
36	1500	16	1890	1759	52	48	190	BFE-1500-16/150

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

09-02-2024