

Blind Flansche
Matrix (Harztyp) Epoxy (Huntsman)
Drilling Standard: JIS B2220 5K



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
1	200	6	320	280	8	23	20	BFE-200-06/5K
2	250	6	385	345	12	23	25	BFE-250-06/5K
3	300	6	440	390	12	23	28	BFE-300-06/5K
4	350	6	510	435	12	25	35	BFE-350-06/5K
5	400	6	570	495	16	25	35	BFE-400-06/5K
6	450	6	620	555	16	25	40	BFE-450-06/5K
7	500	3	674	605	20	25	35	BFE-500-03/5K
8	500	6	674	605	20	25	44	BFE-500-06/5K
9	600	3	784	715	20	27	44	BFE-600-03/5K
10	600	6	784	715	20	27	52	BFE-600-06/5K
11	700	3	875	820	24	27	48	BFE-700-03/5K
12	700	6	875	820	24	27	60	BFE-700-06/5K
13	800	3	995	930	24	33	60	BFE-800-03/5K
14	800	6	995	930	24	33	68	BFE-800-06/5K
15	900	3	1090	1030	24	33	60	BFE-900-03/5K
16	900	6	1090	1030	24	33	78	BFE-900-06/5K

Blind Flansche
Matrix (Harztyp) Epoxy (Huntsman)
Drilling Standard: JIS B2220 5K



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
17	1000	3	1200	1130	28	33	68	BFE-1000-03/5K
18	1000	6	1200	1130	28	33	85	BFE-1000-06/5K
19	1100	3	1355	1240	28	33	74	BFE-1100-03/5K
20	1100	6	1355	1240	28	33	95	BFE-1100-06/5K
21	1200	3	1430	1350	32	33	80	BFE-1200-03/5K
22	1200	6	1430	1350	32	33	105	BFE-1200-06/5K
23	1350	3	1640	1505	32	33	90	BFE-1350-03/5K
24	1350	6	1640	1505	32	33	115	BFE-1350-06/5K
25	1500	3	1740	1660	36	33	100	BFE-1500-03/5K
26	1500	6	1740	1660	36	33	125	BFE-1500-06/5K