

# Rotec Blind Flenzen

Hars Derakane 470

Drilling Standard: EN1092 PN25



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
1	15	25	98	65	4	14	24	BFC-15-25/25
2	20	25	98	75	4	14	24	BFC-20-25/25
3	25	25	116	85	4	14	24	BFC-25-25/25
4	32	25	140	100	4	18	24	BFC-32-25/25
5	40	25	154	110	4	18	24	BFC-40-25/25
6	50	25	164	125	4	18	24	BFC-50-25/25
7	65	25	184	145	4	18	24	BFC-65-25/25
8	80	25	200	160	8	18	28	BFC-80-25/25
9	100	25	228	190	8	22	28	BFC-100-25/25
10	125	25	270	220	8	26	30	BFC-125-25/25
11	150	20	305	250	8	26	30	BFC-150-20/25
12	150	25	305	250	8	26	35	BFC-150-25/25
13	200	20	380	310	12	26	40	BFC-200-20/25
14	200	25	380	310	12	26	44	BFC-200-25/25
15	250	20	430	370	12	30	44	BFC-250-20/25
16	250	25	430	370	12	30	52	BFC-250-25/25

## Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

09-02-2024

# Rotec Blind Flenzen

Hars Derakane 470

Drilling Standard: EN1092 PN25



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
17	300	20	490	430	16	30	52	BFC-300-20/25
18	300	25	490	430	16	30	60	BFC-300-25/25
19	350	20	585	490	16	33	60	BFC-350-20/25
20	350	25	585	490	16	33	68	BFC-350-25/25
21	400	20	640	550	16	36	68	BFC-400-20/25
22	400	25	640	550	16	36	74	BFC-400-25/25
23	500	20	735	660	20	36	80	BFC-500-20/25
24	500	25	735	660	20	36	90	BFC-500-25/25
25	600	20	850	770	20	39	95	BFC-600-20/25
26	600	25	850	770	20	39	105	BFC-600-25/25
27	700	20	960	875	24	42	105	BFC-700-20/25
28	700	25	960	875	24	42	120	BFC-700-25/25
29	800	20	1085	990	24	48	120	BFC-800-20/25
30	800	25	1085	990	24	48	130	BFC-800-25/25
31	900	20	1200	1090	28	48	130	BFC-900-20/25
32	900	25	1200	1090	28	48	145	BFC-900-25/25
33	1000	20	1320	1210	28	56	145	BFC-1000-20/25

## Disclaimer


Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

09-02-2024

## Rotec Blind Flenzen

Hars Derakane 470

Drilling Standard: EN1092 PN25



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
34	1000	25	1320	1210	28	56	160	BFC-1000-25/25
35	1200	20	1540	1420	32	56	170	BFC-1200-20/25

### Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

09-02-2024