

Rotec Blind Flenzen

Hars Epoxy (GRE)

Drilling Standard: AS 2129 Table F



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
1	150	20	305	260	12	22	30	BFE-150-20/AS-F
2	150	25	305	260	12	22	35	BFE-150-25/AS-F
3	150	32	305	260	12	22	40	BFE-150-32/AS-F
4	200	20	380	324	12	22	40	BFE-200-20/AS-F
5	200	25	380	324	12	22	44	BFE-200-25/AS-F
6	200	32	380	324	12	22	48	BFE-200-32/AS-F
7	250	20	430	381	12	26	44	BFE-250-20/AS-F
8	250	25	430	381	12	26	52	BFE-250-25/AS-F
9	250	32	430	381	12	26	60	BFE-250-32/AS-F
10	300	20	490	438	16	26	52	BFE-300-20/AS-F
11	300	25	490	438	16	26	60	BFE-300-25/AS-F
12	300	32	540	438	16	26	68	BFE-300-32/AS-F
13	350	20	585	495	16	30	60	BFE-350-20/AS-F
14	350	25	585	495	16	30	68	BFE-350-25/AS-F
15	350	32	585	495	16	30	74	BFE-350-32/AS-F
16	400	20	640	552	20	30	68	BFE-400-20/AS-F

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

Rotec Blind Flenzen

Hars Epoxy (GRE)

Drilling Standard: AS 2129 Table F



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
17	400	25	640	552	20	30	74	BFE-400-25/AS-F
18	400	32	640	552	20	30	85	BFE-400-32/AS-F
19	450	20	710	610	20	33	74	BFE-450-20/AS-F
20	450	25	710	610	20	33	85	BFE-450-25/AS-F
21	450	32	710	610	20	33	90	BFE-450-32/AS-F
22	500	20	735	673	24	33	80	BFE-500-20/AS-F
23	500	25	735	673	24	33	90	BFE-500-25/AS-F
24	550	20	785	724	24	33	85	BFE-550-20/AS-F
25	550	25	785	724	24	33	100	BFE-550-25/AS-F
26	600	20	850	781	24	36	95	BFE-600-20/AS-F
27	600	25	850	781	24	36	105	BFE-600-25/AS-F
28	700	20	960	857	24	36	110	BFE-700-20/AS-F
29	700	25	960	857	24	36	120	BFE-700-25/AS-F
30	800	20	1085	984	28	36	120	BFE-800-20/AS-F
31	800	25	1085	984	28	36	130	BFE-800-25/AS-F
32	900	20	1200	1105	32	39	130	BFE-900-20/AS-F
33	900	25	1190	1105	32	39	155	BFE-900-25/AS-F

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

09-02-2024

Rotec Blind Flenzen

Hars Epoxy (GRE)

Drilling Standard: AS 2129 Table F



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
34	1000	20	1320	1194	36	39	145	BFE-1000-20/AS-F
35	1000	25	1320	1194	36	39	160	BFE-1000-25/AS-F
36	1200	20	1540	1441	40	42	170	BFE-1200-20/AS-F

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

09-02-2024