

Blind Flenzen
Matrix (hars) Derakane 470
Drilling Standard: EN1092 PN16




#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
1	15	10	98	65	4	14	18	BFC-15-10/16
2	15	16	98	65	4	14	18	BFC-15-16/16
3	20	10	98	75	4	14	18	BFC-20-10/16
4	20	16	98	75	4	14	18	BFC-20-16/16
5	25	10	116	85	4	14	18	BFC-25-10/16
6	25	16	116	85	4	14	20	BFC-25-16/16
7	32	10	140	100	4	18	18	BFC-32-10/16
8	32	16	140	100	4	18	18	BFC-32-16/16
9	40	10	154	110	4	18	18	BFC-40-10/16
10	40	16	154	110	4	18	20	BFC-40-16/16
11	50	10	164	125	4	18	18	BFC-50-10/16
12	50	16	164	125	4	18	20	BFC-50-16/16
13	65	10	184	145	4	18	18	BFC-65-10/16
14	65	16	184	145	4	18	20	BFC-65-16/16
15	80	10	200	160	8	18	22	BFC-80-10/16
16	80	16	200	160	8	18	25	BFC-80-16/16

Blind Flenzen
Matrix (hars) Derakane 470
Drilling Standard: EN1092 PN16




#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
17	100	10	228	180	8	18	22	BFC-100-10/16
18	100	16	228	180	8	18	25	BFC-100-16/16
19	125	10	254	210	8	18	22	BFC-125-10/16
20	125	16	254	210	8	18	22	BFC-125-16/16
21	150	10	285	240	8	22	22	BFC-150-10/16
22	150	16	285	240	8	22	28	BFC-150-16/16
23	200	10	340	295	12	22	25	BFC-200-10/16
24	200	16	340	295	12	22	35	BFC-200-16/16
25	250	10	405	355	12	26	35	BFC-250-10/16
26	250	16	405	355	12	26	40	BFC-250-16/16
27	300	10	460	410	12	26	40	BFC-300-10/16
28	300	16	460	410	12	26	48	BFC-300-16/16
29	350	10	520	470	16	26	40	BFC-350-10/16
30	350	16	520	470	16	26	52	BFC-350-16/16
31	400	10	585	525	16	30	48	BFC-400-10/16
32	400	16	585	525	16	30	60	BFC-400-16/16
33	450	10	640	585	20	30	52	BFC-450-10/16

Blind Flenzen
Matrix (hars) Derakane 470
Drilling Standard: EN1092 PN16



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
34	450	16	640	585	20	30	68	BFC-450-16/16
35	500	10	715	650	20	33	60	BFC-500-10/16
36	500	16	715	650	20	33	74	BFC-500-16/16
37	600	10	840	770	20	36	68	BFC-600-10/16
38	600	16	840	770	20	36	85	BFC-600-16/16
39	700	10	910	840	24	36	74	BFC-700-10/16
40	700	16	910	840	24	36	92	BFC-700-16/16
41	800	10	1025	950	24	39	85	BFC-800-10/16
42	800	16	1025	950	24	39	105	BFC-800-16/16
43	900	10	1125	1050	28	39	95	BFC-900-10/16
44	900	16	1125	1050	28	39	115	BFC-900-16/16
45	1000	10	1255	1170	28	42	105	BFC-1000-10/16
46	1000	16	1255	1170	28	42	130	BFC-1000-16/16
47	1200	10	1484	1390	32	48	120	BFC-1200-10/16
48	1200	16	1484	1390	32	48	155	BFC-1200-16/16
49	1400	10	1685	1590	36	48	140	BFC-1400-10/16
50	1400	16	1685	1590	36	48	175	BFC-1400-16/16

Blind Flenzen
Matrix (hars) Derakane 470
Drilling Standard: EN1092 PN16



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
51	1600	10	1930	1820	40	56	155	BFC-1600-10/16
52	1600	16	1930	1820	40	56	200	BFC-1600-16/16
53	1800	10	2130	2020	44	56	175	BFC-1800-10/16
54	1800	16	2130	2020	44	56	220	BFC-1800-16/16
55	2000	10	2360	2230	48	62	195	BFC-2000-10/16

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

09-02-2024