

Blind Flenzen
Matrix (hars) Derakane 470
Drilling Standard: JIS B2220 10K



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
1	150	10	285	240	8	23	22	BFC-150-10/10K
2	200	10	350	290	12	23	25	BFC-200-10/10K
3	250	10	410	355	12	25	35	BFC-250-10/10K
4	300	10	460	400	16	25	40	BFC-300-10/10K
5	350	10	510	445	16	25	44	BFC-350-10/10K
6	400	10	570	510	16	27	48	BFC-400-10/10K
7	450	10	644	565	20	27	52	BFC-450-10/10K
8	500	3	674	620	20	27	35	BFC-500-03/10K
9	500	10	674	620	20	27	60	BFC-500-10/10K
10	600	3	795	730	24	33	44	BFC-600-03/10K
11	600	10	795	730	24	33	68	BFC-600-10/10K
12	700	3	910	840	24	33	48	BFC-700-03/10K
13	700	10	910	840	24	33	74	BFC-700-10/10K
14	800	3	1025	950	28	33	60	BFC-800-03/10K
15	800	10	1025	950	28	33	85	BFC-800-10/10K
16	900	3	1125	1050	28	33	60	BFC-900-03/10K

Blind Flenzen
Matrix (hars) Derakane 470
Drilling Standard: JIS B2220 10K



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
17	900	6	1125	1050	28	33	78	BFC-900-06/10K
18	900	10	1125	1050	28	33	95	BFC-900-10/10K
19	1000	3	1244	1160	28	39	68	BFC-1000-03/10K
20	1000	6	1244	1160	28	39	85	BFC-1000-06/10K
21	1000	10	1244	1160	28	39	105	BFC-1000-10/10K
22	1100	3	1355	1270	28	39	74	BFC-1100-03/10K
23	1100	6	1355	1270	28	39	95	BFC-1100-06/10K
24	1100	10	1355	1270	28	39	110	BFC-1100-10/10K
25	1200	3	1470	1380	32	39	80	BFC-1200-03/10K
26	1200	6	1470	1380	32	39	105	BFC-1200-06/10K
27	1200	10	1470	1380	32	39	120	BFC-1200-10/10K
28	1350	3	1640	1540	36	45	90	BFC-1350-03/10K
29	1350	6	1640	1540	36	45	115	BFC-1350-06/10K
30	1350	10	1640	1540	36	45	135	BFC-1350-10/10K
31	1500	3	1810	1700	40	45	100	BFC-1500-03/10K
32	1500	6	1810	1700	40	45	125	BFC-1500-06/10K
33	1500	10	1810	1700	40	45	150	BFC-1500-10/10K